

## Wall Bracing Compliance Worksheet

Complete this worksheet or provide equivalent information on the plans submitted with the permit application.

Sketch and dimension the building plan and the wall bracing rectangle(s) per 321.25(8)(b)1. and Figure 321.25-B. Provide and label additional sketches if the building plan/rectangles change at different floor levels.

Indicate applicable Wall Bracing Method for each level (see Table 321.25-G), each labeled rectangle if more than one (see 321.25(8)(c), and amount of bracing (# of braced panels or length of braced wall required) per the respective table (provide additional Tables for additional rectangles as needed):

Rectangle: \_\_\_\_\_ Wall Ht. = \_\_\_\_\_ Roof Pitch = \_\_\_\_\_ Max. Opening Ht. = \_\_\_\_\_ Wind Exp. = \_\_\_\_\_

Walls Supporting:	Intermittent method (LIB, DWB, WSP, SFB, GB, PCP) and # of panels per Table 321.25-I Min. panel width (Table 321.25-G) = _____		Continuous method (CS-WSP, CS-SFB) and total length required per Table 321.25-J Min. panel width (Table 321.25-H) = _____		PF Method (see Figure 321.25-A). Indicate number of PF panels 16-24" wide provided. Min. PF width (Fig. 321.25-A) = _____	
	Long side	Short side	Long side	Short side	Long side	Short side
Roof and ceiling only						
One floor, roof and ceiling						
Two floors, roof and ceiling						

Rectangle: \_\_\_\_\_ Wall Ht. = \_\_\_\_\_ Roof Pitch = \_\_\_\_\_ Max. Opening Ht. = \_\_\_\_\_ Wind Exp. = \_\_\_\_\_

Walls Supporting:	Intermittent method (LIB, DWB, WSP, SFB, GB, PCP) and # of panels per Table 321.25-I Min. panel width (Table 321.25-G) = _____		Continuous method (CS-WSP, CS-SFB) and total length required per Table 321.25-H Min. panel width (Table 321.25-H) = _____		PF Method (see Figure 321.25-A). Indicate number of PF panels 16-24" wide provided. Min. PF width (Fig. 321.25-A) = _____	
	Long side	Short side	Long side	Short Side	Long side	Short side
Roof and ceiling only						
One floor, roof and ceiling						
Two floors, roof and ceiling						

**PF Method:** For Intermittent bracing, per Table 321.25-I footnote 'h', each PF panel (16-24" wide per Figure 321.25-A) counts as 1/2 of a braced wall panel when determining compliance with Table 321.25-I. For Continuously Sheathed bracing, the actual length of each PF panel (16-24" wide per Figure 321.15-A) in feet counts toward the required total length of bracing required. For intermittent or continuous, each PF panel meeting min. required width of Fig. 321.25-A counts spacing requirements as a braced wall panel when evaluating of Fig. 321.25-C.

**Indicate location of required braced wall panels determined above on building plan in compliance with Figure 321.25-C.**